Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date: 08/08/2014

Version:

1.1. Product identifier		
Product form	: Mixture	
Trade name	: FVP NON-CHLORINATED BRAKE CLEANER NON-VOC 15 OZ.	
Product code	: FVPNCBC-15	
1.2. Relevant identified uses of the s	substance or mixture and uses advised against	
Use of the substance/mixture	: Brake Parts Cleaner	
1.3. Details of the supplier of the saf	fety data sheet	
Factory Motor Parts 1380 Corporate center Curve Ste. 200 Eagan, MN 55121 (866) 387-3343		
1.4. Emergency telephone number		
Emergency number	: CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)	
SECTION 2: Hozarda identificatio	N 0	
SECTION 2: Hazards identificatio		
2.1. Classification of the substance	or mixture	
Classification (GHS-US) Flam. Aerosol 2 H223 Compressed gas H280 Acute Tox. 3 (Oral) H301 Skin Irrit. 2 H315 Eye Irrit. 2A H319 Repr. 2 H361 STOT SE 1 H370 STOT SE 3 H336 STOT RE 2 H373 Full text of H-phrases: see section 16		
Label elements GHS-US labeling Hazard pictograms (GHS-US)		
GHS-US labeling	: $i \\ i \\$	
GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US)	 Danger H223 - Flammable aerosol H280 - Contains gas under pressure; may explode if heated H301+H311 - Toxic if swallowed or in contact with skin H315 - Causes skin irritation H319 - Causes serious eye irritation H336 - May cause drowsiness or dizziness H361 - Suspected of damaging fertility or the unborn child H370 - Causes damage to organs 	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

		P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P307+P311 - If exposed: Call a poison center/doctor P308+P313 - If exposed or concerned: Get medical advice/attention P312 - Call a POISON CONTROL CENTER, doctor, if you feel unwell. P314 - Get medical advice/attention if you feel unwell P321 - Specific treatment: See section 4.1 on SDS P330 - Rinse mouth P332+P313 - If skin irritation occurs: Get medical advice/attention P361 - Take off immediately all contaminated clothing P362 - Take off contaminated clothing and wash before reuse P363 - Wash contaminated clothing before reuse P403+P233 - Store in a well-ventilated place. Keep container tightly closed P405 - Store locked up P410+P403 - Protect from sunlight. Store in a well-ventilated place P401+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.
2.2	Other hererde	

Other hazards 2.3.

Other hazards not contributing to the classification

: Contains gas under pressure; may explode if heated.

Unknown acute toxicity (GHS-US) 2.4.

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable 2.2 Mixtur

3.2. Mixture	1		1
Name	Product identifier	%	Classification (GHS-US)
Methanol	(CAS No) 67-56-1	30 - 50	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:dust,mist), H331 STOT SE 1, H370
Acetone	(CAS No) 67-64-1	10 - 30	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Toluene	(CAS No) 108-88-3	10 - 30	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Heptane, Branched Cyclic	(CAS No) 426260-76-6	17.4528 - 18.18	Flam. Liq. 1, H224 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Heptane	(CAS No) 142-82-5	4.545 - 8.181	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Carbon Dioxide, Liquefied, Under Pressure	(CAS No) 124-38-9	5 - 10	Compressed gas, H280

SECTION 4: First aid measures

4.1.	Description of first aid measures		
First-ai	d measures general	:	 Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medica advice/attention. Call a POISON CENTER or doctor/physician.
First-ai	d measures after inhalation	:	Cough. Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.
First-ai	d measures after skin contact	:	Rinse skin with water/shower. Immediately call a POISON CENTER or doctor/physician. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
First-ai	d measures after eye contact	:	Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with wate for several minutes. Immediately call a POISON CENTER or doctor/physician. Obtain medical attention if pain, blinking or redness persist. Direct contact with the eyes is likely to be irritating.
First-ai	d measures after ingestion	:	 Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Immediately call a POISON CENTER or doctor/physician.
05/12/2	014		EN (English LIS) 2/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.2. Most important symptoms and	effects, both acute and delayed
Symptoms/injuries	: Suspected of damaging fertility or the unborn child. Causes damage to organs.
Symptoms/injuries after inhalation	: May cause respiratory irritation. Shortness of breath. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin. Causes skin irritation.
Symptoms/injuries after eye contact	: Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue.
Symptoms/injuries after ingestion	: Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measure	s
5.1. Extinguishing media	
Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.
5.2. Special hazards arising from the	substance or mixture
Fire hazard	: Flammable aerosol.
Explosion hazard	 Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
5.3. Advice for firefighters	
Firefighting instructions	 Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire reaches explosives. Evacuate area.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Aerosol Level 2.
SECTION 6: Accidental release m	easures
	equipment and emergency procedures
General measures	: No naked lights. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove
	ignition sources. Use special care to avoid static electric charges.
6.1.1. For non-emergency personnel	
Protective equipment	: Safety glasses. Gloves.
Emergency procedures	: Evacuate unnecessary personnel.
6.1.2. For emergency responders	
Protective equipment	: Equip cleanup crew with proper protection. Avoid breathing dust,fume,gas,mist,vapor spray.
Emergency procedures	: Ventilate area.
6.2. Environmental precautions	
	otify authorities if liquid enters sewers or public waters.
6.3. Methods and material for contain	ment and cleaning up
For containment	 Dam up the liquid spill. Plug the leak, cut off the supply. Contain released substance, pump into suitable containers.
Methods for cleaning up	: Store away from other materials.
6.4. Reference to other sections	
See Heading 8. Exposure controls and perso	nal protection.
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed	: Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or burn even after use.
Precautions for safe handling	 Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation vapor. Do not spray on an open flame or other ignition source. Obtain special instructions . Do not handle until all safety precautions have been read and understood. Avoid breathing dust, fumes, gas, mist, vapor spray. Use only outdoors or in a well-ventilated area. Do not breathe dust, fumes, gas, mist, vapor spray.
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

res : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7.2. Conditions for safe storage, including any incompatibilities		
Technical measures	: Proper grounding procedures to avoid static electricity should be followed.	
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Keep container tightly closed.	
Incompatible products	: Strong bases. Strong acids.	
Incompatible materials	: Sources of ignition. Direct sunlight. Heat sources.	
Storage area	: Store in a well-ventilated place.	

7.3. Specific end use(s)

Follow Label Directions.

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

Benzene (71-43-2) USA ACGIH				
	,			
USA ACGIH	ACGIH STEL (ppm)	5 ppm		
USA ACGIH	ACGIH Ceiling (ppm)	25 ppm		
USA OSHA	OSHA PEL (TWA) (ppm)	1 ppm		
USA OSHA	OSHA PEL (Ceiling) (ppm)	5 ppm		
Toluene (108-88-3)				
USA ACGIH	ACGIH TWA (mg/m ³)	75 mg/m³		
USA ACGIH	ACGIH TWA (ppm)	20 ppm		
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm		
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm		
Heptane (142-82-5)	·			
USA ACGIH	ACGIH TWA (ppm)	400 ppm		
USA ACGIH	ACGIH STEL (ppm)	400 ppm		
Hentone Brenched Cu				
Heptane, Branched Cyo USA ACGIH	ACGIH TWA (ppm)	400 ppm		
USA ACGIH	ACGIH STEL (ppm)	500 ppm		
USA OSHA	OSHA PEL (TWA) (ppm)	500 ppm		
USA ACGIH	fied, Under Pressure (124-38-9) ACGIH TWA (mg/m ³)	9000 mg/m³		
USA ACGIH	ACGIH TWA (ppm)	5000 ppm		
USA ACGIH	ACGIH STEL (mg/m ³)	54000		
USA ACGIH	ACGIH STEL (ppm)	30000 ppm		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	9000 mg/m ³		
USA OSHA	OSHA PEL (TWA) (ppm)	5000 ppm		
Methanol (67-56-1)				
USA ACGIH	ACGIH TWA (mg/m ³)	262 mg/m ³		
USA ACGIH	ACGIH TWA (ppm)	200 ppm		
USA ACGIH	ACGIH STEL (mg/m ³)	328 mg/m ³		
USA ACGIH	ACGIH STEL (ppm)	250 ppm		
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m ³		
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm		
Acetone (67-64-1)				
USA ACGIH	ACGIH TWA (mg/m ³)	1188 mg/m³		
USA ACGIH	ACGIH TWA (ppm)	500 ppm		
USA ACGIH	ACGIH STEL (mg/m ³)	1782 mg/m ³		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetone (67-64-1)		
USA ACGIH	ACGIH STEL (ppm)	750 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	2400 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

8.2. Exposure controls

Appropriate engineering controls

- Personal protective equipment
- : Local exhaust ventilation, vent hoods.
- : Gloves. Safety glasses. Avoid all unnecessary exposure.



nd protection	: Wear protective gloves.
e protection	: Chemical goggles or safety glasses.
n and body protection	: Wear suitable protective clothing.
spiratory protection	 Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.
ner information	: Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

SECTION 9. Physical and chemical properties		
9.1. Information on basic physical and chemical properties		
Physical state	: Gas	
Appearance	: Liquid.	
Color	: Colourless to light yellow.	
Odor	: Solvent-like odour.	
Odor threshold	: No data available	
рН	: No data available	
Relative evaporation rate (butyl acetate=1)	: No data available	
Melting point	: -95 °C (Lowest Component)	
Freezing point	: No data available	
Boiling point	: 56 °C (Lowest Component)	
Flash point	: -18 °C (Lowest Component)	
Auto-ignition temperature	: 465 °C (Lowest Component)	
Decomposition temperature	: No data available	
Flammability (solid, gas)	: No data available	
Vapor pressure	: No data available	
Relative vapor density at 20 °C	: No data available	
Relative density	: 0.78	
Solubility	: Moderately soluble in water.	
Log Pow	: No data available	
Log Kow	: No data available	
Viscosity, kinematic	: No data available	
Viscosity, dynamic	: No data available	
Explosive properties	: Heating may cause a fire or explosion.	
Oxidizing properties	: No data available	
Explosive limits	: No data available	
9.2. Other information		
VOC content	: 69.3 %	
Gas group	: Liquefied gas	

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	ay, March 26, 2012 / Rules and Regulations
10.3. Possibility of hazardous reactions	3
Not established.	
10.4. Conditions to avoid	
Direct sunlight. Extremely high or low tempera	tures. Heat. Sparks. Open flame. Overheating.
10.5. Incompatible materials	
Strong acids. Strong bases.	
10.6. Hazardous decomposition produc	
Toxic fume Carbon monoxide. Carbon dioxid	16.
SECTION 11: Toxicological inform	ation
11.1. Information on toxicological effect	ts
Acute toxicity	: Toxic if swallowed. Toxic in contact with skin.
Benzene (71-43-2)	
LD50 oral rat	> 930 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; > 2000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	> 8240 mg/kg (Rabbit; Experimental value; 21 CFR 191.10; > 9.4; Rabbit)
LC50 inhalation rat (mg/l)	43.767 mg/l/4h (Rat; Experimental value)
LC50 inhalation rat (ppm)	13700 ppm/4h (Rat; Experimental value)
Toluene (108-88-3)	
LD50 oral rat	5580 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Literature study; 5580 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	> 5000 mg/kg body weight LD50 quoted as 14.1 mL/kg (12267 mg/kg using density of 0.87)
LC50 inhalation rat (mg/l)	> 28.1 mg/l/4h (Rat; Air, Literature study)
Heptane (142-82-5)	
LD50 oral rat	> 15000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; >5000 mg/kg bodyweight; Rat; Read-across)
LD50 dermal rabbit	> 3160 mg/kg (Rabbit; Literature study; Equivalent or similar to OECD 402; >2000 mg/kg bodyweight; Rabbit; Read-across)
LC50 inhalation rat (mg/l)	103 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	25000 ppm/4h (Rat; Literature study)
Heptane, Branched Cyclic (426260-76-6)	
LD50 oral rat	> 15000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; >5000 mg/kg bodyweight; Rat; Read-across)
LD50 dermal rabbit	> 3160 mg/kg (Rabbit; Literature study; Equivalent or similar to OECD 402; >2000 mg/kg bodyweight; Rabbit; Read-across)
LC50 inhalation rat (mg/l)	103 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	25000 ppm/4h (Rat; Literature study)
Methanol (67-56-1)	
LD50 oral rat	>= 2528 mg/kg body weight application as 50% aqueous solution
LD50 dermal rabbit	17100 mg/kg corresponding to 20 ml/kg bw according to the authors
LC50 inhalation rat (mg/l)	128.2 mg/l/4h Air
Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	20000 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	71 mg/l/4h (Rat; Experimental value; 76 mg/l/4h; Rat; Experimental value)
LC50 inhalation rat (ppm)	30000 ppm/4h (Rat; Experimental value)
Skin corrosion/irritation Serious eye damage/irritation	Causes skin irritation. Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Benzene (71-43-2)	
IARC group	1
Toluene (108-88-3)	
IARC group	3

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure)	: Causes damage to organs. May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met. Toxic if swallowed. Toxic in contact with skin.
Symptoms/injuries after inhalation	: May cause respiratory irritation. Shortness of breath. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin. Causes skin irritation.
Symptoms/injuries after eye contact	: Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue.
Symptoms/injuries after ingestion	: Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

SECTION 12: Ecological information

12.1. Toxicity

Benzene (71-43-2)		
LC50 fish 1	5.3 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)	
EC50 Daphnia 1	18 mg/l (24 h; Daphnia magna)	
LC50 fish 2	15.1 mg/l (96 h; Pimephales promelas)	
EC50 Daphnia 2	10 mg/l (48 h; Daphnia magna)	
TLM fish 1	22.5 mg/l (96 h; Lepomis macrochirus; Soft water)	
TLM fish 2	32 mg/l (96 h; Pimephales promelas; Hard water)	
Threshold limit algae 1	100 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)	
Threshold limit algae 2	50 mg/l (24 h; Phaeodactylum; Photosynthesis)	
Acetone (67-64-1)		
TLM fish 1	13000 ppm (96 h; Gambusia affinis; Turbulent water)	
TLM fish 2	> 1000 ppm (96 h; Pisces)	
Threshold limit other aquatic organisms 1	3000 mg/l (Plankton)	
Threshold limit other aquatic organisms 2	28 mg/l (Protozoa)	
Threshold limit algae 1	7500 mg/l (Scenedesmus quadricauda; pH = 7)	
Threshold limit algae 2	3400 mg/l (48 h; Chlorella sp.)	
Toluene (108-88-3)		
LC50 fish 1	24 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)	
EC50 Daphnia 1	84 mg/l (24 h; Daphnia magna; Locomotor effect)	
LC50 fish 2	13 mg/l (96 h; Lepomis macrochirus)	
EC50 Daphnia 2	11.5 - 19.6 mg/l (48 h; Daphnia magna)	
Threshold limit algae 1	> 400 mg/l (168 h; Scenedesmus quadricauda; Toxicity test)	
Threshold limit algae 2	105 mg/l (192 h; Microcystis aeruginosa)	
Heptane (142-82-5)		
LC50 fish 1	375 mg/l (96 h; Tilapia mossambica; Nominal concentration)	
LC50 other aquatic organisms 1	> 1000 mg/l (96 h)	
EC50 Daphnia 1	1.5 mg/l (48 h; Daphnia magna)	
LC50 fish 2	> 100 mg/l (96 h; Oncorhynchus kisutch)	
TLM fish 1	4924 mg/l (48 h; Gambusia affinis)	
Threshold limit other aquatic organisms 1	> 1000 mg/l (96 h)	
Threshold limit algae 1	> 200 mg/l (Scenedesmus quadricauda; Toxicity test)	
Threshold limit algae 2	1.5 mg/l (8 h; Algae; Photosynthesis)	
Carbon Dioxide, Liquefied, Under Pressure (1	24-38-9)	
LC50 fish 1	35 mg/l (96 h; Salmo gairdneri (Oncorhynchus mykiss); Lethal)	
LC50 fish 2	60 - 240 mg/l (12 h; Salmo gairdneri (Oncorhynchus mykiss); Lethal)	
Methanol (67-56-1)		
LC50 fish 1	15400 mg/l (96 h; Lepomis macrochirus; Lethal)	
EC50 Daphnia 1	> 10000 mg/l (48 h; Daphnia magna; Lethal)	
LC50 fish 2	10800 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)	
EC50 Daphnia 2	24500 mg/l (48 h; Daphnia magna; Locomotor effect)	
Threshold limit other aquatic organisms 1	6600 mg/l (16 h; Pseudomonas putida)	
Threshold limit algae 1	530 mg/l (192 h; Microcystis aeruginosa)	

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8000 mg/l (168 h; Scenedesmus quadricauda)			
6210 mg/l (96 h; Pimephales promelas; Nominal concentration)			
8800 mg/l (48 h; Daphnia pulex)			
5540 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)			
13000 ppm (96 h; Gambusia affinis; Turbulent water)			
 > 1000 ppm (96 h; Pisces) 			
3000 mg/l (Plankton)			
28 mg/l (Protozoa)			
7500 mg/l (Scenedesmus quadricauda; pH = 7)			
3400 mg/l (48 h; Chlorella sp.)			
NON-VOC 15 OZ.			
Not established.			
Readily biodegradable in water. Ozonation in water. Forming sediments in water. Biodegradable in the soil. Low potential for adsorption in soil. Photolysis in the air.			
2.18 g O ₂ /g substance			
2.15 g O ₂ /g substance			
3.10 g O ₂ /g substance			
0.70 % ThOD			
·			
Not established.			
Not established.			
Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.			
2.15 g O ₂ /g substance			
2.52 g O ₂ /g substance			
3.13 g O ₂ /g substance			
0.69 % ThOD			
Readily biodegradable in water. Biodegradable in the soil. Adsorbs into the soil.			
1.92 g O ₂ /g substance			
0.06 g O ₂ /g substance			
3.52 g O ₂ /g substance			
> % ThOD (5 day(s)) > 0.5			
May cause long-term adverse effects in the environment.			
24-38-9) Piedegradability: pet applicable. Not applicable (gap)			
Biodegradability: not applicable. Not applicable (gas). Not applicable			
Not applicable			
Not applicable			
Not applicable			
Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.			
$0.6 - 1.12 \text{ g} \text{ O}_2 / \text{g}$ substance			
$1.42 \text{ g } \text{O}_2$ /g substance			
1.5 g O ₂ /g substance			
0.8 % ThOD			
Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test) data on mobility of the substance available. Not			
anaerobic conditions. No (test) data on mobility of the substance available. Not			

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetone (67-64-1) BOD (% of ThOD)

(20 day(s)) 0.872

BOD (% of ThOD)	(20 day(s)) 0.872
12.3. Bioaccumulative potential	
FVP NON-CHLORINATED BRAKE CLEA	ANER NON-VOC 15 OZ.
Bioaccumulative potential	Not established.
•	
Benzene (71-43-2)	40 Optime animali (Opportunitation invaluitation)
BCF fish 1	19 Salmo gairdneri (Oncorhynchus mykiss)
BCF fish 2	< 10 (3 days; Leuciscus idus)
BCF other aquatic organisms 1	30 (24 h; Chlorella sp.; Fresh weight)
Log Pow	2.13 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Acetone (67-64-1)	
Bioaccumulative potential	Not established.
Toluene (108-88-3)	
BCF fish 1	13.2 (Anguilla japonica)
BCF fish 2	90 (72 h; Leuciscus idus)
BCF other aquatic organisms 1	380 (24 h; Chlorella sp.; Fresh weight)
BCF other aquatic organisms 2	4.2 (Mytilus edulis; Fresh weight)
Log Pow	2.73 (Experimental value; Other; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Heptane (142-82-5)	
BCF other aquatic organisms 1	552
Log Pow	4.66 (Experimental value; 4.5; Literature)
Bioaccumulative potential	Potential for bioaccumulation ($4 \ge Log$ Kow ≤ 5).
·	
Heptane, Branched Cyclic (426260-76-6	
Bioaccumulative potential	Not established.
Carbon Dioxide, Liquefied, Under Press	sure (124-38-9)
Log Pow	0.83 (Experimental value)
Bioaccumulative potential	Bioaccumulation: not applicable.
Methanol (67-56-1)	
BCF fish 1	< 10 (72 h; Leuciscus idus)
BCF fish 2	1 (72 h; Cyprinus carpio; Blood)
Log Pow	-0.77 (Experimental value; Other)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Acetone (67-64-1)	
BCF fish 1	0.69 (Pisces)
BCF other aquatic organisms 1	3
Log Pow	-0.24 (Test data)
Bioaccumulative potential	Not bioaccumulative. Not established.
Bioaccumulative potentiai	Not bioaccumulative. Not established.
12.4. Mobility in soil	
Benzene (71-43-2)	
Surface tension	0.029 N/m (20 °C)
Toluene (108-88-3)	
Surface tension	0.03 N/m (20 °C)
Heptane (142-82-5)	
Surface tension	0.020 N/m (20 °C)
Methanol (67-56-1)	
Surface tension	0.023 N/m (20 °C)
Acetone (67-64-1)	
Surface tension	0.0237 N/m (20 °C)
12.5 Other advance offecto	
12.5. Other adverse effects	· Avoid release to the environment
Other information	: Avoid release to the environment.

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal consideration	ns
13.1. Waste treatment methods	
Waste disposal recommendations	Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.
Additional information	: Flammable vapors may accumulate in the container.
Ecology - waste materials	: Avoid release to the environment. Hazardous waste due to toxicity.
SECTION 14: Transport information In accordance with ADR / RID / IMDG / IATA / /	
US DOT (ground): UN1950, Aerosols, 2	2.1, Limited Quantity
ICAO/IATA (air): UN1950, Aerosols, 2	1, Limited Quantity
IMO/IMDG (water): UN1950, Aerosols, 2.	1, Limited Quantity
Special Provisions: N82 - See 173.306 of	this subchapter for classification criteria for flammable aerosols.
14.2. UN proper shipping name	
Proper Shipping Name (DOT)	: Aerosols
	flammable, (each not exceeding 1 L capacity)
Department of Transportation (DOT) Hazard Classes	: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
Hazard labels (DOT)	: 2.1 - Flammable gas
DOT Special Provisions (49 CFR 172.102)	: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Packaging Non Bulk (49 CFR 173.xxx)	: None
DOT Packaging Bulk (49 CFR 173.xxx)	: None
14.3. Additional information	
Other information	: No supplementary information available.
Overland transport No additional information available	
Transport by sea	
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 48 - Stow "away from" sources of heat,87 - Stow "separated from" Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials
Air transport	
DOT Quantity Limitations Passenger aircraft/rai (49 CFR 173.27)	i : 75 kg
DOT Quantity Limitations Cargo aircraft only (4) CFR 175.75)	∂ : 150 kg
SECTION 15: Regulatory informatio	n
15.1. US Federal regulations	
FVP NON-CHLORINATED BRAKE CLEANE	R NON-VOC 15 OZ.
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard Sudden release of pressure hazard
Toluene (108-88-3)	
Listed on United States SARA Section 313 Listed on the United States TSCA (Toxic Subs	tances Control Act) inventory
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard
	Fire hazard Immediate (acute) health hazard

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Heptane, Branched Cyclic (426260-76-6)		
Not listed on the United States TSCA (Toxic Substances Control Act) inventory		
Not listed of the Officed States TSCA (Toxic Subs	tances Control Act) Inventory	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard	
Methanol (67-56-1)		
Listed on United States SARA Section 313 Listed on the United States TSCA (Toxic Substan	ces Control Act) inventory	
SARA Section 311/312 Hazard Classes Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard		
Acetone (67-64-1)		
Listed on the United States TSCA (Toxic Substan	ces Control Act) inventory	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard Delayed (chronic) health hazard	

15.2. International regulations

CANADA

FVP NON-CHLORINATED BRAKE CLEANER NON-VOC 15 OZ.		
WHMIS Classification	Class B Division 5 - Flammable Aerosol	
Toluene (108-88-3)		
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects	
Heptane, Branched Cyclic (426260-76-6)		
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
Methanol (67-56-1)		
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
Acetone (67-64-1)		
Listed on the Canadian DSL (Domestic Sustances	s List)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects	

EU-Regulations

Toluene (108-88-3)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Acetone (67-64-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)- Directive 79/831/EEC, sixth Amendment of Directive 67/548/EEC (dangerous substances) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Repr.Cat.3; R63 F; R11 T; R23/24/25 T; R39/23/24/25 Xn; R48/20 Xi; R36/38 Full text of R-phrases: see section 16

15.2.2. National regulations

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetone (67-64-1)

- Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on KECI (Korean Existing Chemicals Inventory) Listed on AICS (Australian Inventory of Chemical Substances)
- Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
- Listed on the Korean ECL (Existing Chemicals List)

15.3. US State regulations

FVP NON-CHLORINATED BRAKE CLEANER NON-VOC 15 OZ. State or local regulations U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

Acetone (67-64-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes				

Toluene (108-88-3)

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

Acetone (67-64-1)

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

: None.

Benzene 71-43-2

U.S. - Massachusetts - Right To Know List

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

SECTION 16: Other information

Other information Full text of H-phrases: see section 16:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Compressed gas	Gases under pressure Compressed gas
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Aerosol 2	Flammable aerosol Category 2
Flam. Liq. 1	Flammable liquids Category 1
Flam. Liq. 2	Flammable liquids Category 2
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H223	Flammable aerosol
H224	Extremely flammable liquid and vapor
H225	Highly flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H301	Toxic if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H331	Toxic if inhaled
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H370	Causes damage to organs

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

NFPA health hazard	: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
NFPA fire hazard	: 3 - Liquids and solids that can be ignited under almost all ambient conditions.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
HMIS III Rating	
Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 3 Serious Hazard
Physical	: 1 Slight Hazard
Personal Protection	: B

SDS US (GHS HazCom 2012) - TCC

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.