# Safety Data Sheet

\* Trusted Quality Since 1921 \* www.rustoleum.com

1. Identification			
Product Name:	PTOUCH QT 2PK SEMIGL BLACK	Revision Date:	10/9/2017
Product Identifier:	1974502	Supercedes Date:	5/15/2015
Product Use/Class:	Topcoat/Waterbased Acrylic		
Supplier:	Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA	Manufacturer:	Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA
Preparer:	Regulatory Department		
Emergency Telephone:	y Telephone: 24 Hour Hotline: 847-367-7700		

# 2. Hazard Identification

## Classification

Symbol(s) of Product



Signal Word Danger

#### Possible Hazards

4% of the mixture consists of ingredient(s) of unknown acute toxicity.

GHS HAZARD STATEMENTS Carcinogenicity, category 1A	H350	May cause cancer.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
GHS LABEL PRECAUTIONARY STATE		l instructions before use.
P280	Wear protecti	ve gloves/protective clothing/eye protection/face protection.
P308+P313	IF exposed or	concerned: Get medical advice/attention.
P405	Store locked	Jp.

Date Printed: 10/9/2017		Page 2 / 6
P501	Dispose of contents/container in accordance with local, regional and national regulations	3.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.	
P272	Contaminated work clothing should not be allowed out of the workplace.	
P302+P352	IF ON SKIN: Wash with plenty of soap and water.	
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.	
P321	For specific treatment see label	
GHS ADDITIONAL INFORMATION H362	Contains one or more Category 1 or Category 2 Reproductive Toxicants at greater than Safety Data Sheet shall be available for the mixture upon request.	0.1%. A

## GHS SDS PRECAUTIONARY STATEMENTS

P363 Wash contaminated clothing before reuse.

## 3. Composition / Information On Ingredients

#### HAZARDOUS SUBSTANCES

Chemical Name	CAS-No.	<u>Wt.%</u> <u>Range</u>	GHS Symbols	GHS Statements
Dipropylene Glycol Monobutyl Ether	29911-28-2	2.5-10	Not Available	Not Available
Ethanol	64-17-5	1.0-2.5	GHS02	H225
Carbon Black	1333-86-4	0.1-1.0	Not Available	Not Available
Sodium Nitrite	7632-00-0	0.1-1.0	GHS03-GHS06- GHS08	H272-301-319-331-350
N-Methyl 2-Pyrrolidone	872-50-4	0.1-1.0	GHS06-GHS08	H315-319-331-335-360
5-Chloro-2-Methyl-4-Isothiazolin-3-one Mixture with 2-Methyl-4-Isothiazolin-3-one	55965-84-9	<0.1	GHS05-GHS06	H301-311-314-317-331

# 4. First-Aid Measures

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

FIRST AID - SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

**FIRST AID - INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

**FIRST AID - INGESTION:** Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention. If swallowed, rinse mouth with water. If feeling unwell, get medical attention.

#### Page 3 / 6

## 5. Fire-Fighting Measures

EXTINGUISHING MEDIA: Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** No unusual fire or explosion hazards noted. Keep containers tightly closed. FLASH POINT IS TESTED TO BE GREATER THAN 200 DEGREES F.

SPECIAL FIREFIGHTING PROCEDURES: Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

## 6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers

# 7. Handling and Storage

**HANDLING:** Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing. **STORAGE:** Store in a dry, well ventilated place. Keep container tightly closed when not in use.

## 8. Exposure Controls / Personal Protection

OSHA PEL- CEILING
02.2.110
N.E.
N.E.

## PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

**RESPIRATORY PROTECTION:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

SKIN PROTECTION: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

**OTHER PROTECTIVE EQUIPMENT:** Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

**HYGIENIC PRACTICES:** Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

# 9. Physical and Chemical Properties

Appearance:	Liquid	Physical State:	Liquid
Odor:	Mild	Odor Threshold:	N.E.
Relative Density:	1.045	pH:	N.D.
Freeze Point, °C:	N.D.	Viscosity:	N.D.
Solubility in Water:	Miscible	Partition Coefficient, n-octanol/	
Decompostion Temp., °C:	N.D.	water:	N.D.
Boiling Range, °C:	64 - 537	Explosive Limits, vol%:	1.1 - 36.0
Flammability:	Does not Support Combustion	Flash Point, °C:	94
Evaporation Rate:	Slower than Ether	Auto-ignition Temp., °C:	N.D.
Vapor Density:	Heavier than Air	Vapor Pressure:	N.D.

(See "Other information" Section for abbreviation legend)

# 10. Stability and Reactivity

CONDITIONS TO AVOID: No Information

**INCOMPATIBILITY:** Incompatible with strong oxidizing agents, strong acids and strong alkalies.

HAZARDOUS DECOMPOSITION: When heated to decomposition, it emits acrid smoke and irritating fumes.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

**STABILITY:** This product is stable under normal storage conditions.

# 11. Toxicological Information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Irritating, and may injure eye tissue if not removed promptly.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Low hazard for usual industrial handling or commercial handling by trained personnel.

**EFFECTS OF OVEREXPOSURE - INHALATION:** High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist.

EFFECTS OF OVEREXPOSURE - INGESTION: Substance may be harmful if swallowed.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** Contains carbon black. Chronic inflammation, lung fibrosis, and lung tumors have been observed in some rats experimentally exposed for long periods of time to excessive concentrations of carbon black and several insoluble fine dust particles. Tumors have not been observed in other animal species (i.e., mouse and hamster) under similar circumstances and study conditions. Epidemiological studies of North American workers show no evidence of clinically significant adverse health effects due to occupational exposure to carbon black.

Carbon black is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC and is proposed to be listed as A4- "not classified as a human carcinogen" by the American Conference of Governmental Industrial Hygienists. Significant exposure is not anticipated during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of carbon black in the formula.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

#### ACUTE TOXICITY VALUES The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
64-17-5	Ethanol	7060 mg/kg Rat	15,800 mg/kg Rabbit	30,000 mg/l Rat
1333-86-4	Carbon Black	>15400 mg/kg Rat	N.I.	N.I.
7632-00-0	Sodium Nitrite	85 mg/kg Rat	N.I.	5.5 mg/L Rat
872-50-4	N-Methyl 2-Pyrrolidone	3914 mg/kg Rat	8000 mg/kg Rabbit	>5.1 mg/L Rat
55965-84-9	5-Chloro-2-Methyl-4-Isothiazolin-3-one Mixture with 2-Methyl-4-Isothiazolin-3-one	53 mg/kg Rat	N.I.	N.I.

N.I. - No Information

# 12. Ecological Information

ECOLOGICAL INFORMATION: Product is a mixture of listed components.

# 13. Disposal Information

**DISPOSAL INFORMATION:** No Information

## 14. Transport Information

	Domestic (USDOT)	International (IMDG)	<u>Air (IATA)</u>	<u>TDG (Canada)</u>
UN Number:	N.A.	N.A.	N.A.	N.A.
Proper Shipping Name:	Not Regulated	Not Regulated	Not Regulated	Not Regulated
Hazard Class:	N.A.	N.A.	N.A.	N.A.
Packing Group:	N.A.	N.A.	N.A.	N.A.
Limited Quantity:	No	No	No	No

# 15. Regulatory Information

## **U.S. Federal Regulations:**

## **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

#### No Information

### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name	<u>CAS-No.</u>
Sodium Nitrite	7632-00-0
N-Methyl 2-Pyrrolidone	872-50-4

#### **Toxic Substances Control Act:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

## **Chemical Name**

Sodium Nitrite No TSCA 12(b) components exist in this product. <u>CAS-No.</u> 7632-00-0

# 16. Other Information

HMIS RA <sup>-</sup> Health:	TINGS 2*	Flammability:	1	Physical Hazard:	0	Personal Protection:	х
NFPA RA Health:	TINGS 2	Flammability:	1	Instability	0		
VOLATILE	ORGA	NIC COMPOUN	DS, g/L:	252			
SDS REVI	SION D	ATE:	10/9/2017				
REASON FOR REVISION:		Substance a 01 - Identifi 02 - Hazarc 05 - Fire-fig 09 - Physic	I Identification hting Measures al & Chemical Properties tory Information nformation	Changed	in Section(s):		

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.