

# **Delta Technical Coatings, Inc.**

# **Material Safety Data Sheet**

IDENTITY (As Used so label and Link		1						
IDENTITY (As Used on label and List)	Note: Blank spaces are not permitted. If any item is not applicable, or no							
Acrylic Gloss Finish Spray by Delta	information is ava	information is available, the space must be marked to indicate that.						
SECTION I		1						
Manufacturer's Name	Emergency Telep							
Alchemco Inc.	(800) 423-4							
Address			er for Information					
1916 Augusta Ct.			(562) 695-7969					
	Date Prepared							
Ontario, California 91761		Rev. 1/31/0	Rev. 1/31/05					
SECTION II - Hazardous Ingredients/Identify Informa	ation							
Hazardous Components (Specific Chemical Identity; Common Name(s))			OSHA PEL	ACGIH TLV	Other Limits	% by wt.		
Methylene Chloride (cas#75-09-2)			N/A	100ppm	N/A	20		
Isobutane Propane (cas# 68476-85-7)		N/A	800ppm	N/A	22			
loopatane i repane (each ee ii e ee i)			14//	осорріні	14/71			
Toluene (cas# 108-88-3)		N/A	150ppm	N/A	38			
10.00.00 (0.00.00.00)			,,, .	.оорр	,,,			
Acrylic Resin (cas# 25013-15-4)			N/A	N/A	N/A	20		
,			· · · · · · · · · · · · · · · · · · ·					
SECTION III -Physical/Chemical Characteristics								
Boiling Point		Specific Gravity (	H <sub>2</sub> O = 1)		T			
·	N/A	1				0.787		
Vapor Pressure (PSIG)		Melting Point						
, , ,	40-59 @ 70F	Ŭ				N/A		
Vapor Density (AIR = 1)		Evaporation Rate (Water = 1)						
						>1		
Solubility in Water					<u></u>			
Insoluble								
Appearance and Odor								
A clear liquid with a strong solvent odor.								
SECTION IV -Fire and Explosion Hazard Data								
Flash Point (Method Used)		Flammable Limits	<b>S</b>		LEL	UEL		
	<25F TCC	;		N/A	N/A	N/A		
Extinguishing Media				•		•		
Dry chemical, CO2, water fog or standard foam.								
Special Fire Fighting Procedures								
Exposure to temperatures over 120F may cause	bursting or venting	g. Keep cont	ainer cool. Us	e equipment or :	sheilding to pr	otect		
	<u> </u>				<u> </u>			
personnel against bursting or venting containers.	Do not puncture of	or incinerate	container.					
Unusual Fire and Explosion Hazards	•							
Do not use near sparks, open flame or while smo	king.							
	<u> </u>							

**SECTION V -Reactivity Data** 

## MSDS000011

Stability	Unstable		Conditions to Avoid				
Do not store above 120F.							
	Stable	X					
Incompatability (Materials t	o Avoid)	•	•				
N/A	or Dunne dunte						
Hazardous Decomposition N/A	or Byproducts		1				
Hazardous	May Occur		Conditions to Avoid N/A				
Polymerization	Will Not Occur		IN/A				
		Х					
SECTION VI -Health	h Hazard Data						
Route(s) of Entry:				Inhalation?	Yes	Skin?	Ingestion?
Health Hazards (Acute and							
May be harmful or	fatal if swallow	ed. May	cause eye or	skin irritation			
Carcinogenicity:				NTP?		IARC Monographs	OSHA Regulated?
					Yes	No	Yes
Signs and Symptoms of Ex	posure						
		from va	apors in poorly	ventilated ar	eas may include ir	ritation of the mucous membra	ines of
the nose, throat a	nd respiratory tr	act and	symptoms of h	eadache an	d nausea.		
Skin & Eye: Proloi	nged and repea	ted con	tact with produc	ct may cause	e skin irritation. Pro	olonged contact with product m	nay result
in and implestion							
in eye irritation.							
Ingestion: Nausea	and/or vomiting	g may o	ccur if ingested	l.			
Medical Conditions Genera	Illy Aggravated by Expo	sure					
N/A							_
Emergency and First Aid P							
Inhalation: Move s	subject to fresh	air. Eye	contact: Flush	eyes with a	large amount of w	vater for at least 15 minutes. Co	onsult
a physician if irrita	tion persists. Sl	kin Con	tact: Wash affe	cted areas th	noroughly with soa	p and water. Consult a physici	an if
irritation persists.	Ingestion: If swa	allowed,	give two glass	es of water t	o drink. Consult a	physician. Never give anything	յ by
mouth to an uncor	nscious person.	DO NO	T INDUCE VO	MITING!			
	·						

# SECTION VII -Precautions for Safe Handling and Use

Steps To Be Taken in Case Material Is Released or Spilled

Control spill with paper towel. Dried refuse may be disposed of according to local, state and federal regulations.

Do not puncture	or incinerate	empty or full cans.

Waste Disposal Method

Dried refuse may be disposed of according to local, state and federal regulations. Check with local authorities for details on

disposal.

Precautions to Be Taken in Handling and Storing

Avoid storing in areas exposed to direct sunlight. Keep from freezing temperatures. Store in a cool, dry place.

Other Precautions

Keep lid on can when not in use.

### KEEP OUT OF REACH OF CHILDREN.

#### **SECTION VIII - Control Measures**

Respiratory Protection (Specify Type)

Ventilation	Local Exhaust	Special
	Yes	NIOSH approved vapor respirator
	Mechanical (General)	Other
	Yes	None

Protective Gloves

Impervious plastic or rubber.

Protective Glasses

Safety glasses may be worn to avoid eye contact.

Other Protective Clothing or Equipment

Long sleeve garments may be worn to avoid contact with skin.

Work/Hygenic Practices

Clean-up with soap and water. Wash hands with soap and water after using product. Place cap back on container tightly.

#### **SECTION IX - Disclaimer**

Delta Technical Coatings, Inc. Assumes no responsibility for personal injury or property damage to vendees,

users or third parties caused by the product. Such vendees assumes all risks associated with the use of this product.

#### **HMIS SYMBOL**

# HEALTH2FLAMMABILITY4REACTIVITY1

#### **RATING**

SEVERE 4 SERIOUS 3 MODERATE 2 SLIGHT 1 MINIMAL 0

## **Transportation Information:**

D.O.T.: Consumer Commodity

I.A.T.A.: ORM-D Air