Material Safety Data Sheet

U.S. Department of Labor

May be used to comply with

OSHA's Hazard Communication Standard, 29 CFR 1910.1200 Standard must be consulted for specific requirements.

Occupational Safety and Health Administration (Non-Mandatory Form)

s. Form Approved OMB No. 1218-0072

| IDENTITY (As Used on Label and List) Oil Based Block Printing Ink (3450-3460, 3550-3556) | Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that. |
|---|---|
| Section I Manufacturer's Name Speedball Art Products, LLC | Emergency Telephone Number 704-838-1475 |
| Address (Number, Street, City, State, and ZIP Code) 2301 Speedball Road Statesville, NC 28677 USA | Telephone Number for Information 704-838-1475 |
| Date Prepared: January 2, 2013 | Signature of Preparer (optional) |

Section II - Hazardous Ingredients/Identity Information

| Hazardous Components (Specific Chemical Identity; Common Name(s)): | OSHA PEL | ACGIH TLV | Other Limits | %(optional) |
|--|----------|-----------|-----------------|-------------|
| Mineral Spirits (CAS #8052-41-3) | N/A | 500pp | Recommended N/A | 3.5-9.9% |

Product labeling conforms to ASTM D-4236. Approved for the AP seal as per the Art & Craft Materials Institute, Inc. (ACMI). Note: This product has been certified to be non-toxic. This product has been evaluated by a Toxicologist only as per intended usage. DO NOT DEVIATE FROM INTENDED USE.

Section III - Physical/Chemical Characteristics

| Boiling Point | 275°F-410°F | Specific Gravity (H ₂ O = 1) | .96-1.62 |
|-------------------------|----------------|---|------------------------|
| Vapor Pressure (mm Hg.) | Unknown | Melting Point | N/A |
| Vapor Density (AIR = 1) | Greater than 1 | Evaporation Rate (Butyl Acetate = 1) | N/A |
| Solubility in Water | Not soluble | Appearance and Odor | Paste with slight odor |

Section IV - Fire and Explosion Hazard Data

| Flash Point (Method Used) Greater than 105°F TCC | Flammable Limits N/A | LEL N/A | UEL N/A |
|---|------------------------------------|----------------------|--------------------|
| Extinguishing Media Water spray, dry chemical, foam & carbon dio | | 17/11 | 1771 |
| Special Fire Fighting Procedures Wear self-contained breathing apparatus (pres gear. Use water to keep fire-exposed containers | ** | ved or equivalent) a | nd full protective |
| Unusual Fire and Explosion Hazards Rags and waste paper containing this material material in metal cans with tight lids. | may heat and burn spontaneously. S | Store wiping rags co | ontaining this |

(Reproduce locally) OSHA 174, Sept. 1985

Section V - Reactivity Data

Oil Based Block Printing Ink

Page 2

| Stability | Unstable | | Conditions to Avoid None known. |
|--|-----------|---------------------|---------------------------------|
| Incompatibility (Materials to Avoid) Avoid contact with strong oxidizing agents | | | |
| Hazardous Decomposition or Byproducts Usual products of combustion-carbon monoxide & carbon monoxide | | | |
| Hazardous Polymerization | May Occur | Will Not Occur ✓ | Conditions to Avoid N/A |

Section VI - Health Hazard Data

| Route(s) of Entry: | Inhalation? | Skin? | Ingestion? | | |
|---|-------------|-----------------------------------|-----------------------|--|--|
| | See below | Irritation with prolonged contact | N/A | | |
| Health Hazards (Acute and Chronic) Solvent vapor can cause headache, dizziness & nausea. Eye contact: can cause irritation and transient corneal injury. Overexposure can cause central nervous system effects. | | | | | |
| Carcinogenicity: N/A | NTP? N/A | IARC Monographs? N/A | OSHA Regulated? N/A | | |
| Signs and Symptoms of Exposure N/A | | | | | |
| Medical Conditions Generally Aggravated by Exposure Pre-existing skin, eye, and respiratory disorders. | | | | | |
| Emergency and First Aid Procedures Contact with eyes: Flush with w induce vomiting, contact doctor. | | | ter. Ingestion-do NOT | | |

Section VII - Precautions for Safe Handling and Use

| Steps to Be Taken in Case Material is Released or Spilled Large spills should be diked and absorbed on inert material such as sand. |
|--|
| Waste Disposal Method Incineration at permitted facility. Observe all Federal, State and local laws concerning health and environment. |
| Precautions to Be taken in Handling and Storing Treat as flammable material. |
| Other Precautions N/A |

Section VIII - Control Measures

| Respiratory Protection (Specify Type) None required with adequate ventilation & normal usage conditions. | | | | |
|--|--------------------------|-------------|--|--|
| Ventilation | Local Exhaust N/A | Special N/A | | |
| | Mechanical (General) N/A | Other N/A | | |
| Protective Gloves Impervious Eye Protection Safety Glasses or goggles | | | | |
| Other Protective Clothing or Equipment Eyewash fountains and safety showers must be accessible. | | | | |
| Work/Hygienic Practices Use protective cream where excessive skin contact is likely. | | | | |