

Gold Eagle - Sta-Bil Storage Fuel Stabiliser

Trico Products

Chemwatch: 4789-34

Version No: 4.1.1.1

Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 1

Issue Date: 24/02/2014

Print Date: 01/08/2014

Initial Date: Not Available

S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Gold Eagle - Sta-Bil Storage Fuel Stabiliser
Chemical Name	Not Applicable
Synonyms	118 ml Bottle (PN: 27222), 236 ml Bottle (PN: 27223), 473 ml Bottle (PN: 27228), Pack Size:, formerly : Gold Eagle - Sta-Bil Fuel Stabiliser
Proper shipping name	Not Applicable
Chemical formula	Not Applicable
Other means of identification	Not Available
CAS number	Not Applicable

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Fuel stabiliser for gasoline powered engines.
--------------------------	---

Details of the manufacturer/importer

Registered company name	Trico Products	Gold Eagle
Address	Unit 1, 80 Fairbank Road Clayton 3169 VIC Australia	4400 South Kildare Avenue Chicago 60632 IL United States
Telephone	+61 3 9271 3288	+1 312 376 4400
Fax	+61 3 9271 3290	Not Available
Website	http://www.tricoproducts.com	Not Available
Email	sales@tricoproducts.com.au	marketing@goldeagle.com

Emergency telephone number

Association / Organisation	Not Available	Not Available
Emergency telephone numbers	+61 3 9271 3288	+1 800 535 5053
Other emergency telephone numbers	+61 3 9271 3288	+1 800 535 5053

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the Model WHS Regulations and the ADG Code.

COMBUSTIBLE LIQUID, regulated for storage purposes only

CHEMWATCH HAZARD RATINGS

	Min	Max
Flammability	1	1
Toxicity	1	1
Body Contact	1	1
Reactivity	1	1
Chronic	0	0


0 = Minimum
1 = Low
2 = Moderate
3 = High
4 = Extreme

Poisons Schedule S5

Gold Eagle - Sta-Bil Storage Fuel Stabiliser

GHS Classification ^[1] Flammable Liquid Category 4, STOT - SE (Narcosis) Category 3, Aspiration Hazard Category 1, Acute Aquatic Hazard Category 3, Chronic Aquatic Hazard Category 3
Legend: 1. Classified by Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

Label elements



SIGNAL WORD DANGER

Hazard statement(s)

- H227 Combustible liquid
- H336 May cause drowsiness or dizziness
- H304 May be fatal if swallowed and enters airways
- H402 Harmful to aquatic life
- H412 Harmful to aquatic life with long lasting effects

Precautionary statement(s): Prevention

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P271 Use only outdoors or in a well-ventilated area.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P273 Avoid release to the environment.

Precautionary statement(s): Response

- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider
- P331 Do NOT induce vomiting.
- P370+P378 In case of fire: Use... to extinguish.
- P312 Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.

Precautionary statement(s): Storage

- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s): Disposal

- P501 Dispose of contents/container to authorised chemical landfill or if organic to high temperature incineration

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
64742-47-8,	95	<u>isoparaffins petroleum hydrotreated HFP</u>
Not Available	5	additives

SECTION 4 FIRST AID MEASURES

Gold Eagle - Sta-Bil Storage Fuel Stabiliser

	<ul style="list-style-type: none">› Wash out immediately with fresh running water.› Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.› Seek medical attention without delay; if pain persists or recurs seek medical attention.› Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none">› Immediately remove all contaminated clothing, including footwear.› Flush skin and hair with running water (and soap if available).› Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none">› If fumes or combustion products are inhaled remove from contaminated area.› Lay patient down. Keep warm and rested.› Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.› Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.› Transport to hospital, or doctor.
Ingestion	<ul style="list-style-type: none">› For advice, contact a Poisons Information Centre or a doctor at once.› Urgent hospital treatment is likely to be needed.› If swallowed do NOT induce vomiting.› If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.› Observe the patient carefully.› Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.› Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.› Transport to hospital or doctor without delay.

Requirement of any immediate medical attention and special treatment needed

- For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:
- › Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
 - › Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO₂ 50 mm Hg) should be intubated.
 - › Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
 - › A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
 - › Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.
 - › Lavage is indicated in patients who require decontamination; ensure use of cuffed endotracheal tube in adult patients. [Ellenhorn and Barceloux: Medical Toxicology]

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- › Foam.
- › Dry chemical powder.
- › BCF (where regulations permit).
- › Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility

- › Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc.

Gold Eagle - Sta-Bil Storage Fuel Stabiliser

Fire Fighting	<ul style="list-style-type: none"> ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear full body protective clothing with breathing apparatus. ▶ Prevent, by any means available, spillage from entering drains or water course. ▶ Use water delivered as a fine spray to control fire and cool adjacent area.
Fire/Explosion Hazard	<ul style="list-style-type: none"> ▶ Combustible. ▶ Slight fire hazard when exposed to heat or flame. ▶ Heating may cause expansion or decomposition leading to violent rupture of containers. ▶ On combustion, may emit toxic fumes of carbon monoxide (CO).

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills	<ul style="list-style-type: none"> ▶ Remove all ignition sources. ▶ Clean up all spills immediately. ▶ Avoid breathing vapours and contact with skin and eyes. ▶ Control personal contact with the substance, by using protective equipment.
Major Spills	<p>Moderate hazard.</p> <ul style="list-style-type: none"> ▶ Clear area of personnel and move upwind. ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	<ul style="list-style-type: none"> ▶ Containers, even those that have been emptied, may contain explosive vapours. ▶ Do NOT cut, drill, grind, weld or perform similar operations on or near containers. ▶ Electrostatic discharge may be generated during pumping - this may result in fire. ▶ Ensure electrical continuity by bonding and grounding (earthing) all equipment.
Other information	<ul style="list-style-type: none"> ▶ Store in original containers. ▶ Keep containers securely sealed. ▶ No smoking, naked lights or ignition sources. ▶ Store in a cool, dry, well-ventilated area.

Conditions for safe storage, including any incompatibilities

Suitable container	<ul style="list-style-type: none"> ▶ Metal can or drum ▶ Packaging as recommended by manufacturer. ▶ Check all containers are clearly labelled and free from leaks.
Storage incompatibility	<ul style="list-style-type: none"> ▶ Avoid reaction with oxidising agents

PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA


Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	isoparaffins petroleum hydrotreated HFP	White spirits	790 mg/m3	Not Available	Not Available	(see Chapter 16)

EMERGENCY LIMITS

Gold Eagle - Sta-Bil Storage Fuel Stabiliser

Ingredient	Original IDLH	Revised IDLH
Isoparaffins petroleum hydrotreated HFP	29,500 mg/m3	20,000 mg/m3
additives	Not Available	Not Available

Exposure controls

Appropriate engineering controls	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <ul style="list-style-type: none"> Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.
Personal protection	
Eye and face protection	<ul style="list-style-type: none"> Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
Skin protection	<p>See Hand protection below</p> <ul style="list-style-type: none"> Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber
Hands/feet protection	<p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p>
Body protection	<p>See Other protection below</p> <ul style="list-style-type: none"> Overalls.
Other protection	<ul style="list-style-type: none"> P.V.C. apron. Barrier cream.
Thermal hazards	Not Available

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the: "Forsberg Clothing Performance Index". The effect(s) of the following substance(s) are taken into account in the computer-generated selection: Gold Eagle - Sta-Bil Storage Fuel Stabiliser Not Available

Material	CPI
* CPI - Chemwatch Performance Index	
A: Best Selection	
B: Satisfactory; may degrade after 4 hours continuous immersion	
C: Poor to Dangerous Choice for other than short term immersion	
E: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -	
* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.	

Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS	-	A-PAPR-AUS / Class 1
up to 50 x ES	-	A-AUS / Class 1	-
up to 100 x ES	-	A-2	A-PAPR-2 ^

^ - Full-face
A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3),

Gold Eagle - Sta-Bil Storage Fuel Stabiliser

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Red liquid with a solvent odour; does not mix with water.		
Physical state	Liquid	Relative density (Water = 1)	0.9
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	82	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	84 (TOC)	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Combustible.	Oxidising properties	Not Available
Upper Explosive Limit (%)	7.0	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	0.8	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution(1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> ▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo. There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.
Ingestion	Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733) Accidental ingestion of the material may be damaging to the health of the individual.
Skin Contact	The liquid may be miscible with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives . Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.

Gold Eagle - Sta-Bil Storage Fuel Stabiliser

Chronic
Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.
There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.
Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin.

Gold Eagle - Sta-Bil Storage Fuel Stabiliser	TOXICITY	IRRITATION
	Not Available	Not Available
isoparaffins petroleum hydrotreated HFP	TOXICITY	IRRITATION
	Not Available	Not Available

* Value obtained from manufacturer's msds unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances

Gold Eagle - Sta-Bil Storage Fuel Stabiliser, ISOPARAFFINS PETROLEUM HYDROTREATED HFP
No significant acute toxicological data identified in literature search.

Acute Toxicity	☉	Carcinogenicity	☉
Skin Irritation/Corrosion	☉	Reproductivity	☉
Serious Eye Damage/Irritation	☉	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	☉	STOT - Repeated Exposure	☉
Mutagenicity	☉	Aspiration Hazard	✓

Legend: ✓ – Data required to make classification available
✗ – Data available but does not fill the criteria for classification
☉ – Data Not Available to make classification

CMR STATUS

Not Applicable

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

DO NOT discharge into sewer or waterways.
Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
Not Available	Not Available	Not Available

Bioaccumulative potential

Ingredient	Bioaccumulation
Available	Not Available

Mobility in soil

Ingredient	Mobility
Not Available	Not Available

SECTION 13 DISPOSAL CONSIDERATIONS

Gold Eagle - Sta-Bil Storage Fuel Stabiliser

refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate:

- › Reduction
- › Reuse
- › Recycling
- › Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.

SECTION 14 TRANSPORT INFORMATION

Labels Required

COMBUSTIBLE LIQUID

COMBUSTIBLE LIQUID, regulated for storage purposes only

Marine Pollutant

NO

HAZCHEM

Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL 73 / 78 and the IBC code

Source	Ingredient	Pollution Category
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	Isoparaffins petroleum hydrotreated HFP	Y

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

Isoparaffins petroleum hydrotreated HFP(64742-47-8,) is found on the following regulatory lists

"International Council of Chemical Associations (ICCA) - High Production Volume List", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "International Maritime Dangerous Goods Requirements (IMDG Code)", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "Australia Exposure Standards", "FisherTransport Information", "Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO", "Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (English)", "OECD List of High Production Volume (HPV) Chemicals", "Australia Inventory of Chemical Substances (AICS)", "Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (Dutch)", "International Chemical Secretariat (ChemSec) SIN List (*Substitute It Now!)", "International Society of Automotive Engineers (SAE) Declarable Substances Chemical List - ARP9536", "OECD Existing Chemicals Database", "Sigma-Aldrich Transport Information", "Australia High Volume Industrial Chemical List (HVICL)", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Spanish)", "Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "International Air Transport Association (IATA) Dangerous Goods Regulations", "Australia Hazardous Substances Information System - Consolidated Lists", "International Fragrance Association (IFRA) Survey: Transparency List", "IMO IBC Code Chapter 17: Summary of minimum requirements", "Australia - New South Wales Protection of the Environment Operations (Waste) Regulation 2005 - Characteristics of trackable wastes"

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references

Gold Eagle - Sta-Bil Storage Fuel Stabiliser

(M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.